



SAFETY DATA SHEET

UFR UNIVERSAL FLUX REMOVER, AEROSOL

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name UFR UNIVERSAL FLUX REMOVER, AEROSOL

Product number MCC-UFR10A, MCC-UFR107, MCC-UFR10Y

Recommended use of the chemical and restrictions on use

Application Cleaning agent.

Details of the supplier of the safety data sheet

Supplier MICROCARE CORPORATION

Manufacturer MICROCARE CORPORATION

595 John Downey Drive
New Britain, CT 06051
United States of America
CAGE: OATV9
Tel: + 1 800 638 0125, +1 860-827-0626
Fax: +1 860-893-1930
techsupport@microcare.com

Emergency telephone number

Emergency telephone CHEMTREC 1-800-424-9300 (within the U.S.)
+1 703-741-5970 (from anywhere in the world)

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status This Product is Not Hazardous under the OSHA Hazard Communication Standard.

Physical hazards Not Classified

Health hazards Repr. 1B - H360

Human health Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. Mild dermatitis, allergic skin rash.

Environmental The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Physicochemical Vapors are heavier than air and may travel along the floor and accumulate in the bottom of containers. Not considered to be a significant hazard due to the small quantities used. Gas or vapor displaces oxygen available for breathing (asphyxiant).

Label elements

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Pictogram



Signal word

Danger

Hazard statements

H360 May damage fertility or the unborn child.

Precautionary statements

P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C /122°F.

P501 Dispose of contents/ container in accordance with local regulations.

Supplemental label information

Safety data sheet available on request. For use in industrial installations only.

Contains

METHANOL

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

trans-1-Chloro-3,3,3-trifluoropropene CAS number: 102687-65-0	60-100%
Classification Press. Gas, Liquefied - H280	
TRANS-1,3,3,3-TETRAFLUOROPROP-1-ENE CAS number: 29118-24-9	10-30%
Classification Press. Gas, Liquefied - H280	
ETHANOL CAS number: 64-17-5	1-5%
Classification Flam. Liq. 2 - H225	

UFR UNIVERSAL FLUX REMOVER, AEROSOL

METHANOL	<1%
CAS number: 67-56-1	
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 3 - H301	
Acute Tox. 3 - H311	
Acute Tox. 3 - H331	
Eye Irrit. 2A - H319	
Repr. 1B - H360	
STOT SE 1 - H370	
ISOBUTYL METHYL KETONE	<1%
CAS number: 108-10-1	
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H332	
Eye Irrit. 2A - H319	
STOT SE 3 - H335	
ETHYL ACETATE	<1%
CAS number: 141-78-6	
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2A - H319	
STOT SE 3 - H336	

The full text for all hazard statements is displayed in Section 16.

Composition comments TSCA: The ingredients of this product are on the TSCA Inventory. The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of CFR 1900.1200 TSCA: The ingredients of this product are on the TSCA Inventory.

Composition

4. First-aid measures

Description of first aid measures

General information	Never give anything by mouth to an unconscious person. Do not induce vomiting. Place unconscious person on the side in the recovery position and ensure breathing can take place. If breathing stops, provide artificial respiration. Consult a physician for specific advice.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
Ingestion	Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Promptly get affected person to drink large volumes of water to dilute the swallowed chemical. Get medical attention.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Skin Contact	Remove contaminated clothing and rinse skin thoroughly with water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Consult a physician for specific advice.
<u>Most important symptoms and effects, both acute and delayed</u>	
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Get medical attention promptly if symptoms occur after washing.
Inhalation	Upper respiratory irritation. Vapors are heavier than air and may travel along the floor and accumulate in the bottom of containers. Gas or vapor displaces oxygen available for breathing (asphyxiant). Prolonged or excessive inhalation may cause respiratory tract irritation.
Ingestion	May cause stomach pain or vomiting. Diarrhea. May cause nausea, headache, dizziness and intoxication. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Skin contact	Skin irritation. This product is rapidly absorbed through the skin and may cause symptoms similar to those of ingestion.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. May cause blurred vision and serious eye damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

Special hazards arising from the substance or mixture

Specific hazards	Keep away from heat, sparks and open flame. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapors. Aerosol containers can explode when heated, due to excessive pressure build-up.
Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. Oxides of carbon. Fire or high temperatures create: Carbonyl compounds. Mineral acids.
<u>Advice for firefighters</u>	
Protective actions during firefighting	Move containers from fire area if it can be done without risk. Bursting aerosol containers may be propelled from a fire at high speed.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. Avoid inhalation of vapors. Use approved respirator if air contamination is above an acceptable level.
<u>Environmental precautions</u>	
Environmental precautions	Contain spillage with sand, earth or other suitable non-combustible material. Avoid release to the environment.

Methods and material for containment and cleaning up

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Methods for cleaning up Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions Provide adequate ventilation. Avoid inhalation of vapors/spray and contact with skin and eyes. Keep away from heat, sparks and open flame. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapors. Keep out of the reach of children.

Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

Reference to other sections. Store away from incompatible materials (see Section 10).

8. Exposure controls/Personal protection

Control parameters

Occupational exposure limits

trans-1-Chloro-3,3,3-trifluoropropene

Long-term exposure limit (8-hour TWA): SUP 800 ppm

ETHANOL

Short-term exposure limit (15-minute): ACGIH 1000 ppm 1880 mg/m³
A3

Long-term exposure limit (8-hour TWA): OSHA 1000 ppm 1900 mg/m³

METHANOL

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 262 mg/m³

Short-term exposure limit (15-minute): ACGIH 250 ppm 328 mg/m³
Sk

Long-term exposure limit (8-hour TWA): OSHA 200 ppm 260 mg/m³

ISOBUTYL METHYL KETONE

Long-term exposure limit (8-hour TWA): ACGIH 20 ppm 82 mg/m³

Short-term exposure limit (15-minute): ACGIH 75 ppm 307 mg/m³
A3

Long-term exposure limit (8-hour TWA): OSHA 100 ppm 410 mg/m³

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): ACGIH 400 ppm 1440 mg/m³

Long-term exposure limit (8-hour TWA): OSHA 400 ppm 1400 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.
A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.
OSHA = Occupational Safety and Health Administration.
Sk = Danger of cutaneous absorption.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Additional Occupational Exposure Limits

Ingredient comments ACGIH = US Standard. SUP = Supplier's recommendation. OES = Occupational Exposure Standard.

trans-1-Chloro-3,3,3-trifluoropropene (CAS: 102687-65-0)

Ingredient comments No exposure limits known for ingredient(s).

ETHANOL (CAS: 64-17-5)

Ingredient comments WEL = Workplace Exposure Limits

METHANOL (CAS: 67-56-1)

Biological limit values 15 mg/l

Exposure controls

Protective equipment



Appropriate engineering controls

No specific ventilation requirements. This product must not be handled in a confined space without adequate ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber).

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination. Wear apron or protective clothing in case of contact.

Hygiene measures

No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products. When using do not eat, drink or smoke.

Respiratory protection

Considering the size of the packaging, the risk is regarded as minimal. Vapors are heavier than air and may travel along the floor and accumulate in the bottom of containers. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Wear self-contained breathing apparatus with full facepiece.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Aerosol. Liquid. Gas
Color	Clear liquid. Colorless.
Odor	Slight.
Odor threshold	No information available.
pH	Not applicable.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Melting point	Not applicable.
Initial boiling point and range	19°C/66°F @ 101.3 kPa
Flash point	Not applicable. The product is not flammable.
Evaporation rate	Not determined.
Evaporation factor	No information available.
Upper/lower flammability or explosive limits	Not applicable.
Other flammability	No information available.
Vapor pressure	1.91 kPa @ 20°C
Vapor density	>1
Relative density	1.24
Bulk density	No information available.
Solubility(ies)	Slightly soluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.
Refractive index	No information available.
Particle size	No information available.
Molecular weight	No information available.
Volatility	100%
Saturation concentration	No information available.
Critical temperature	No information available.
Volatile organic compound	This product contains a maximum VOC content of 59 g/litre.
Flammability	The product is not flammable.

10. Stability and reactivity

Reactivity	There are no known reactivity hazards associated with this product.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Will not polymerize.
Conditions to avoid	Keep away from heat, sparks and open flame. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapors.
Materials to avoid	Alkali metals. Alkaline earth metals.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Hazardous decomposition products Heating may generate the following products: Toxic and corrosive gases or vapors. Halogenated hydrocarbons. Hydrogen fluoride (HF). Carbon dioxide (CO₂). Carbon monoxide (CO).

11. Toxicological information

Information on toxicological effects

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - oral

ATE oral (mg/kg) 50,384.18

Acute toxicity - dermal

ATE dermal (mg/kg) 151,152.54

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 1,511.53

ATE inhalation (dusts/mists mg/l) 251.92

Inhalation Vapors may irritate throat/respiratory system. A single exposure may cause the following adverse effects: Coughing. Difficulty in breathing.

Ingestion May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.

Skin Contact Product has a defatting effect on skin. May cause allergic contact eczema.

Eye contact May cause temporary eye irritation.

Medical Symptoms Gas or vapor in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.

Toxicological information on ingredients.

trans-1-Chloro-3,3,3-trifluoropropene

Acute toxicity - oral

Notes (oral LD₅₀) No information available.

Acute toxicity - dermal

Notes (dermal LD₅₀) No information required.

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ gases ppmV) 120,000.0

Species Rat

ATE inhalation (gases ppm) 120,000.0

Inhalation Vapors may irritate throat/respiratory system. A single exposure may cause the following adverse effects: Coughing. Difficulty in breathing.

Ingestion May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Skin Contact	Product has a defatting effect on skin. May cause allergic contact eczema.
Eye contact	May cause temporary eye irritation.
Medical Symptoms	Gas or vapor in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.

TRANS-1,3,3,3-TETRAFLUOROPROP-1-ENE

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l)	207,000.0
Species	Rat
ATE inhalation (vapours mg/l)	207,000.0

ETHANOL

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l)	20,000.0
ATE inhalation (vapours mg/l)	20,000.0

Carcinogenicity

IARC carcinogenicity	IARC Group 1 Carcinogenic to humans.
-----------------------------	--------------------------------------

METHANOL

Acute toxicity - oral

Notes (oral LD₅₀)	Acute Tox. 3 - H301 Toxic if swallowed.
ATE oral (mg/kg)	100.0

Acute toxicity - dermal

Notes (dermal LD₅₀)	Acute Tox. 3 - H311 Toxic in contact with skin.
ATE dermal (mg/kg)	300.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀)	Acute Tox. 3 - H331 Toxic if inhaled.
ATE inhalation (vapours mg/l)	3.0
ATE inhalation (dusts/mists mg/l)	0.5

Skin corrosion/irritation

Animal data	Based on available data the classification criteria are not met.
--------------------	--

Serious eye damage/irritation

Serious eye damage/irritation	Based on available data the classification criteria are not met.
--------------------------------------	--

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 1 - H370 Causes damage to organs .

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

A single exposure may cause the following adverse effects: Drowsiness, dizziness, disorientation, vertigo. Unconsciousness. High concentrations may be fatal.

Ingestion

May cause stomach pain or vomiting. May cause severe internal injury.

Skin Contact

A single exposure may cause the following adverse effects: Pain.

Eye contact

No specific symptoms known.

Route of exposure

Ingestion Inhalation Skin and/or eye contact

Target Organs

No specific target organs known.

ISOBUTYL METHYL KETONE

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

ATE inhalation (dusts/mists mg/l) 1.5

Carcinogenicity

IARC carcinogenicity IARC Group 2B Possibly carcinogenic to humans.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

12. Ecological information

Ecotoxicity There are no data on the ecotoxicity of this product.

Ecological information on ingredients.

trans-1-Chloro-3,3,3-trifluoropropene

Ecotoxicity The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

METHANOL

Ecotoxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

Ecological information on ingredients.

trans-1-Chloro-3,3,3-trifluoropropene

Acute aquatic toxicity

Acute toxicity - fish , : , Oncorhynchus mykiss (Rainbow trout)
LC₅₀, 96 hours: 38 mg/l mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 82 mg/l, Freshwater invertebrates

Acute toxicity - aquatic plants EC₅₀, 72 hours: 106.7 mg/l, Freshwater algae
NOEC, 72 hours: 115 mg/l, Freshwater algae

TRANS-1,3,3,3-TETRAFLUOROPROP-1-ENE

Acute aquatic toxicity

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >160 mg/l, Daphnia magna

ETHANOL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: >10,000 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 7,800 mg/l, Daphnia magna

Acute toxicity - aquatic plants , 96 hours: 1000 mg/l, Freshwater algae

METHANOL

Toxicity Based on available data the classification criteria are not met.

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: >100 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >10000 mg/l, Daphnia magna

Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Ecological information on ingredients.

trans-1-Chloro-3,3,3-trifluoropropene

Persistence and degradability The product is not readily biodegradable.

TRANS-1,3,3,3-TETRAFLUOROPROP-1-ENE

Persistence and degradability The product is not readily biodegradable.

ETHANOL

Persistence and degradability The product is expected to be biodegradable.

METHANOL

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients.

trans-1-Chloro-3,3,3-trifluoropropene

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient Kow: 2.09

ETHANOL

Bio-Accumulative Potential Bioaccumulation is unlikely.

Partition coefficient No information available.

METHANOL

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient : -0.77

Mobility in soil

Mobility The product contains volatile substances which may spread in the atmosphere.

Ecological information on ingredients.

trans-1-Chloro-3,3,3-trifluoropropene

Mobility No data available.

ETHANOL

Mobility The product is soluble in water.

UFR UNIVERSAL FLUX REMOVER, AEROSOL**METHANOL**

Mobility No data available.

Other adverse effects

Other adverse effects The product contains a substance which has a photochemical ozone creation potential.

Ecological information on ingredients.**trans-1-Chloro-3,3,3-trifluoropropene**

Other adverse effects None known.

METHANOL

Other adverse effects None known.

13. Disposal considerations**Waste treatment methods**

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Empty containers must not be punctured or incinerated because of the risk of an explosion. Aerosol containers can explode when heated, due to excessive pressure build-up. Reuse or recycle products wherever possible.

14. Transport information**UN Number**

UN No. (TDG) 1950
UN No. (IMDG) 1950
UN No. (ICAO) 1950
UN No. (DOT) UN1950

UN proper shipping name

Proper shipping name (TDG) AEROSOLS
Proper shipping name (IMDG) AEROSOLS
Proper shipping name (ICAO) AEROSOLS
Proper shipping name (DOT) AEROSOLS

Transport hazard class(es)

DOT hazard class 2.2
DOT hazard label 2.2
TDG class 2.2
TDG label(s) 2.2
IMDG Class 2.2
ICAO class/division 2.2

UFR UNIVERSAL FLUX REMOVER, AEROSOL

Transport labels



DOT transport labels



Packing group

TDG Packing Group None

IMDG packing group None

ICAO packing group None

DOT packing group None

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

EmS F-D, S-U

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

Guidance Workplace Exposure Limits EH40.
Introduction to Local Exhaust Ventilation HS(G)37.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

Not listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

Not listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

Not listed.

SARA 313 Emission Reporting

Not listed.

CAA Accidental Release Prevention

Not listed.

SARA (311/312) Hazard Categories

Acute
Pressure

UFR UNIVERSAL FLUX REMOVER, AEROSOL

OSHA Highly Hazardous Chemicals

Not listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

Not listed.

California Air Toxics "Hot Spots" (A-I)

Not listed.

California Air Toxics "Hot Spots" (A-II)

Not listed.

California Directors List of Hazardous Substances

ETHANOL

Present.

Massachusetts "Right To Know" List

ETHANOL

Present.

Rhode Island "Right To Know" List

ETHANOL

Present.

Minnesota "Right To Know" List

ETHANOL

Present.

New Jersey "Right To Know" List

ETHANOL

Present.

Pennsylvania "Right To Know" List

ETHANOL

Present.

Inventories

Canada - DSL/NDSL

ETHANOL

DSL

TRANS-1,3,3,3-TETRAFLUOROPROP-1-ENE

DSL

trans-1-Chloro-3,3,3-trifluoropropene

DSL

US - TSCA

Yes

ETHANOL

Present.

UFR UNIVERSAL FLUX REMOVER, AEROSOL

TRANS-1,3,3,3-TETRAFLUOROPROP-1-ENE

Present.

trans-1-Chloro-3,3,3-trifluoropropene

Present.

16. Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	1/3/2019
Revision	35
Supersedes date	4/7/2017
SDS No.	AEROSOL - UFR
SDS status	Approved.
Hazard statements in full	<p>H225 Highly flammable liquid and vapor.</p> <p>H280 Contains gas under pressure; may explode if heated.</p> <p>H301 Toxic if swallowed.</p> <p>H311 Toxic in contact with skin.</p> <p>H319 Causes serious eye irritation.</p> <p>H331 Toxic if inhaled.</p> <p>H332 Harmful if inhaled.</p> <p>H335 May cause respiratory irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H360 May damage fertility or the unborn child.</p> <p>H370 Causes damage to organs .</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.